

ELECTRIC PALLET TRUCK

PE13



PE 13

TECHNICAL DETAILS

| | | | | |
|-------------------|---|-----------------|----|--------|
| CAPACITY | Q | Nominal load | Kg | 1300 |
| CENTER OF GRAVITY | C | Distance | mm | 600 |
| DRIVING SYSTEM | | Escort/Standing | | Escort |

DIMENSIONS

| | | | | |
|-----------------|------|------------------------|----|----------|
| ELEVATION | h3 | Elevation | mm | 205 |
| | h2 | Normal free elevation | mm | 115 |
| LENGTH | l | Fork length | mm | 1150 |
| | nxS1 | Fork width x thickness | mm | 160 x 44 |
| DIMENSIONS | L | Total length | mm | 1570 |
| | L2 | Steer unit length | mm | 420 |
| | B | Width | mm | 704 |
| | Wa | | mm | 1384 |
| TURNING RADIUS | Wa | | mm | 1384 |
| STOWAGE PASSAGE | Ast | 800x1200 | mm | 1540 |

PERFORMANCES

| | | | |
|------------------------|-------------------------------|------|---------------|
| SPEED | Translation with/without load | km/h | 4,6 / 5,9 |
| LIFTING | with/without load | m/s | 0,056 / 0,06 |
| DESCENT | with/without load | m/s | 0,057 / 0,059 |
| MAX SUPERABLE GRADIENT | With/without load | % | 5 / 7 |

FRAME

| | | | |
|-----------------|------------------------------|-----|----------|
| WHEELS | Driver side/load | Nr | 1 M / 4 |
| TYRES | Driver side/load | | P+ P |
| | Drive wheel dimensions | mmØ | 252 x 63 |
| | Stabilizer wheels dimensions | mmØ | 80 x 58 |
| OPERATING BRAKE | | | Electric |

ELECTRICAL EQUIPMENT

| | | | |
|-----------------|------------------|------|------------|
| ELECTRIC MOTORS | Traction motor | kW | 0,6 |
| | Lifting motor | kW | 0,8 |
| SPEED CONTROL | | | Electronic |
| BATTERY | | | Traction |
| | Voltage/capacity | V/Ah | 24/60 |
| CHARGER | | V-A | 24/20 |

P=Polyurethane

